

Aicci T1 tables specifications



Aicci T1 tables

	XS	S	M	L	XL
Width	33 cm / 13,0"	43 cm / 16,9"	53 cm / 20,9"	63 cm / 24,8"	83 cm / 32,7"
Depth	43 cm / 16,9"	43 cm / 16,9"	43 cm / 16,9"	63 cm / 24,8"	83 cm / 32,7"
Hight	43 cm / 16,9"	49 cm / 19,3"	55 cm / 21,7"	31 cm / 12,2"	37 cm / 14,6"
Glass tabletop	8,0 mm / 0,32" laminated	8,0mm / 0,32" laminated	8,0mm / 0,32" laminated	8,0mm / 0,32" laminated	8,0mm / 0,32" laminated
Glass tabletop finishig	Satin with rounded edges	Satin with rounded edge	Satin with rounded edges	Satin with rounded edges	Satin with rounded edges
Tabletop base thickness	17 mm / 0,67"	17 mm / 0,67"	17 mm / 0,67"	17 mm / 0,67"	17 mm / 0,67"
Table legs diameter	16 mm / 0,63"	16 mm / 0,63"	16 mm / 0,63"	16 mm / 0,63"	16 mm / 0,63"
Corner joint	Titanium	Titanium	Titanium	Titanium	Titanium
Other metal parts	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Light optics	Acrylic	Acrylic	Acrylic	Acrylic	Acrylic
Finishing	Powder coated	Powder coated	Powder coated	Powder coated	Powder coated
Colour	RAL9016 Trafic White	RAL9016 Trafic White	RAL9016 Trafic White	RAL9016 Trafic White	RAL9016 Trafic White
	RAL9005 Jet Black	RAL9005 Jet Black	RAL9005 Jet Black	RAL9005 Jet Black	RAL9005 Jet Black
Weight	5,0 kg	6,2kg	7,5kg	12,0kg	20,0kg
Protection class	IP 40 / tabletop IP 44	IP 40 / tabletop IP 44	IP 40 / tabletop IP 44	IP 40 / tabletop IP 44	IP 40 / tabletop IP 44
Operating temperature	0 C ^o - +45 C ^o	0 C ^o - +45 C ^o	0 C ^o - +45 C ^o	0 C ^o - +45 C ^o	0 C ^o - +45 C ^o

Package

	XS	S	M	L	XL
Material	Ecological cardboard	Ecological cardboard	Ecological cardboard	Ecological cardboard	Ecological cardboard
Width	10 cm / 3,9 "	10 cm / 3,9 "	10 cm / 3,9 "	10 cm / 3,9 "	10 cm / 3,9 "
Lenght	58 cm / 22,8"	58 cm / 22,8"	58 cm / 22,8"	68 cm / 26,8"	88 cm / 34,6"
Hight	47 cm / 18,5"	47 cm / 18,5"	47 cm / 18,5"	67 cm / 26,4"	87 cm / 34,2"
Weight	6,7 kg	7,9 kg	9,2 kg	14,1 kg	23,3 kg

Aicci T1 tables light and electrical specifications



Tunable white LEDs (CCT)

	XS	S	M	L	XL
Colour temperature	2000 - 6500K	2000 - 6500K	2000 - 6500K	2000 - 6500K	2000 - 6500K
Luminous flux	900 lm	900 lm	1130 lm	1360 lm	1810 lm
Colour rendering index	2000K Ra>80/6500K Ra>90	2000K Ra>80/6500K Ra>90	2000K Ra>80/6500K Ra>90	2000K Ra>80/6500K Ra>90	2000K Ra>80/6500K Ra>90
Power	7,7 W	7,7 W	9,6 W	11,5 W	15,4 W
Voltage	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC
Energy consumption/1000 h	8,5 kWh	8,5 kWh	10,6 kWh	12,7 kWh	16,9 kWh
Life cycle B80L50C1	>60.000 h	>60.000 h	>60.000 h	>60.000 h	>60.000h

Colour LEDs (RGB)

	XS	S	M	L	XL
Light colour	16 million colors	16 million colours	16 million colours	16 million colours	16 million colours
Luminous flux	960 lm	960 lm	1200 lm	1440 lm	1920 lm
Power	11,5 W	11,5 W	14,4 W	17,3 W	23,0 W
Voltage	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC
Energy consumption/1000 h	12,7 kWh	12,7 kWh	15,8 kWh	19,0 kWh	25,3 kWh
Life cycle B70L50	>50.000 h	>50.000 h	>50.000 h	>50.000 h	>50.000 h

Controll gear

T1-2-PS1 Birch plywood case

Width	13 cm / 5,1"	AC plug	CEE 7/7 (EU)	Light control	Casambi
Depth	13 cm / 5,1"	Input voltage	85 VAC - 305 VAC	Connection cable lenght	2,5 m / 7,6 ft
Hight	4 cm / 1,6"	Input voltage frequency	47 Hz - 440 Hz	Connection cable	Extremely flexible, PVC
Weight	0,4 kg	Maksimum power	31,2 W	Connection cable diameter	4,5 mm / 0,17"
Protection class	IP 40	Output voltage	24 VDC	Case and cable colour	White / Black
Operation temperature	0 C° - +45 C°	Output current	1,3 A	Life cycle	30.000 h