



Technical specifications AICCI PL1 XL pendant panel light

Made in Muurame, Finland by AICCI.
Design from Finland certified
Finnish Key Flag certified

Materials and colour

Frame and mounting casa: PECF certified
birch from Finland
Shade fabric: Trevira CS
Microprismatic diffuser: acrylic
Light optics: acrylic
Suspension cables: steel

Dimensions

Panel size L1850 x W550mm, 18 kg
L72.8" x W21.7", 39.7 lb

Classifications

Unified glare rating: UGR 16
Enclosing class: IP20
Protection class: II
Energy efficiency class D,
ELR 2019/2015, 1.9.2021-
CE marked

Electrical specifications

Input voltage: 220-240 VAC
Frequency: 50/60 HZ
Maximum power: 90 W
Output voltage: 24 VDC
Output current: 3,75 A

Lighting data

Control: on/off, dimming, Casambi, DALI
or DMX, or another project specific

Tunable white LED lights
Colour temperature: 2000-6500 K
Light Intensity: 7500 lm
Power consumption (maximum): 69.2 W
Consumption/1000h: 76 kWh
Colour rendering index (CRI): >90
Lifetime L80B50C1: >60 000 h
Efficiency: 2000K, 91lm/W / 6500K, 145lm/W

Warranty

5-year limited manufacturer's warranty

Maintainability

The pendant panel light structure can be opened and maintained. LED lights, controller and control gear are replaceable by qualified person.

